

# Redexim



C L E A N I N G



## SandMaster

The SandMaster is a one-pass aerator and slit drainage machine that allows the use of wet or dry sand, gravel or other soil amendments.

The SandMaster mounted behind the Verti-Quake will create deep slits using vibrating coulters knives that leave playing fields ready for play.

FEATURE	BENEFIT
Deep working depth	Improved drainage
De-compacts and fills in one pass	Two functions in one
Works with wet or dry sand	No need for kiln dry material
Very little surface disturbance	No disruption of play
Creates permanent channels	Improves quality of turf
The Verti-Quake can be run separately	Aerate, root prune, decompact

# SandMaster



SPECIFICATIONS	DESCRIPTION
Operational width	62" (1.56 m)
Operating depth	8" (0-200 mm)
Tractor speed measured at 540 rpm at PTO	0.3 - 0.9 mph (0.5 - 1.5 Km/h)
PTO rpm: (max.)	540
Weight	4376.2 lbs / 1985 Kg (without Verti-Quake 2516) 5732 lbs / 2600 Kg (with Verti-Quake 2516)
Number of Filling coulters	6
Distance between the Filling coulters	10" (260 mm)
Thickness of the Filling coulters	1" (25 mm)
Recommended tractor	Min. 65-90 hp with four-wheel drive
Maximum operating capacity	25,833 ft <sup>2</sup> /h (2400 m <sup>2</sup> /h)
Dimensions (with Verti-Quake 2516)	167.7"x89"x74.8" 4.26x2.26x1.90m
Hopper loading height	75" (1.9m) (Elevated machine) 51" (1.3m) (Deepest operating position)
Hopper capacity	53cu. ft. (1.5m <sup>3</sup> )
Hydraulic connection valve	- 1 single operating valve (Elevating the machine) - 2 double operating valves (Conveyor drive) Flow min. 15 l/min (4 Gallon/min)

